

G9 - BI-PIN & MR8 Clear & Frost

G9 BI-PIN

- Clear & frost
- 120 volt
- Protected against ultraviolet rays



G9 CLEAR

← 0.55" →



G9 FROST

↑ 1.78" ↓



G9 >>

Item #	Description	Lamp Type	Base	Color/Finish	Watts	Volts	Hours	MOL	Pkg.
66025	Q25G9PIN	G9	G9 Bi-Pin	Clear	25	120	2,000	1.78	12/120
66030	Q25G9PIN/FR	G9	G9 Bi-Pin	Frost	25	120	2,000	1.78	12/120
66070	Q40G9PIN	G9	G9 Bi-Pin	Clear	40	120	2,000	1.78	12/120
66075	Q40G9PIN/FR	G9	G9 Bi-Pin	Frost	40	120	2,000	1.78	12/120
66035	Q60G9PIN	G9	G9 Bi-Pin	Clear	60	120	2,000	1.78	12/120
66040	Q60G9PIN/FR	G9	G9 Bi-Pin	Frost	60	120	2,000	1.78	12/120

MR8 MINI REFLECTOR

- Flood & spot
- 12 volt
- Protected against ultraviolet rays

← 1.00" →



MR8

↑ 1.36" ↓

MR8 >>

Item #	Description	Lamp Type	Base	Color/Finish	Watts	Volts	Hours	MOL	Pkg.
03192	20MR8/ FL	MR8	G4	Open	20	12	2,000	1.36	24/120
03194	20MR8/ SP	MR8	G4	Open	20	12	2,000	1.36	24/120
03196	35MR8/ FL	MR8	G4	Open	35	12	2,000	1.36	24/120
03197	35MR8/SP	MR8	G4	Open	35	12	2,000	1.36	24/120