

PAR30 & PAR38 120 & 130 Volts

HALOGEN



PAR 30



PAR 30 / SPOT

PAR 30 & 38

- Narrow flood, flood & spot
- Medium base
- 120 & 130 volt



PAR 38



PAR 38 / SPOT



PAR30 120 & 130 VOLT >>

Item #	Description	Lamp Type	Base	Beam Spread	Watts	Volts	Hours	MOL	Pkg.
25100	50PAR30/HAL/FL	PAR30	Medium	Flood 40°	50	120	2,000	3.50	15
25101	50PAR30/HAL/FL/3	PAR30	Medium	Flood 40°	50	130	2,000	3.50	15
25125	50PAR30/HAL/NSP	PAR30	Medium	Narrow Spot 9°	50	120	2,000	3.50	15
25150	75PAR30/HAL/FL	PAR30	Medium	Flood 40°	75	120	2,000	3.50	15
25151	75PAR30/HAL/NFL/3	PAR30	Medium	Narrow Flood 30°	75	130	2,000	3.50	15
25175	75PAR30/HAL/NSP	PAR30	Medium	Narrow Spot 9°	75	120	2,000	3.50	15

PAR38 120 & 130 VOLT >>

Item #	Description	Lamp Type	Base	Beam Spread	Watts	Volts	Hours	MOL	Pkg.
25205	45PAR38/HAL/FL	PAR38	Medium	Flood 30°	45	120	2,000	5.03	15
25200	90PAR38/HAL/FL	PAR38	Medium	Flood 30°	90	120	2,000	5.03	15
25201	90PAR38/HAL/FL/3	PAR38	Medium	Flood 30°	90	130	2,000	5.03	15
25225	90PAR38/HAL/SP	PAR38	Medium	Spot 12°	90	120	2,000	5.03	15
25210	120PAR38/HAL/FL	PAR38	Medium	Flood 30°	120	120	2,000	5.03	15
25211	120PAR38/HAL/FL/3	PAR38	Medium	Flood 30°	120	130	2,000	5.03	15