

### FEATURES AND BENEFITS

- Various cell/lens configurations available
- Easy access plate for quick wiring
- Quick Connect Adapter

### ADDITIONAL OPTIONS

- Emergency battery backup
- Chrome reflector

### APPLICATIONS

Premium grade surface mounted ceiling luminaire with a limitless range of applications. For use in indoor applications where aesthetics and quality are important. Designed for schools, offices, commercial and public buildings.

## 2X2 SURFACE

### S-2X2-2-FB032T8U6-120V-SPL • 90291

2 x 2 Surface Luminaire  
Standard Prismatic Lens  
24" (L) • 24" (W) • 5" (D) • 120 Volt  
Uses Two FBO32T8U6 Lamps\*

### S-2X2-2-FB032T8U6-120V-A09 • 90289

2 x 2 Surface Luminaire  
9 Cell Aluminum Parabolic Louver  
24" (L) • 24" (W) • 5" (D) • 120 Volt  
Uses Two FBO32T8U6 Lamps\*



## 2X4 SURFACE

### S-2X4-3-F32T8-120V-A18 • 90286

2 x 4 Surface Luminaire  
18 Cell Aluminum Parabolic Louver  
48" (L) • 24" (W) • 5" (D) • 120 Volt  
Uses Three F32T8 Lamps\*

### S-2X4-4-F32T8-MV-SPL • 90296

2 x 4 Surface Luminaire  
Standard Prismatic Lens  
48" (L) • 24" (W) • 5" (D) • Multi Volt  
Uses Four F32T8 Lamps\*

### S-2X4-4-F32T8-MV-A18 • 90298

2 x 4 Surface Luminaire  
18 Cell Aluminum Parabolic Louver  
48" (L) • 24" (W) • 5" (D) • Multi Volt  
Uses Four F32T8 Lamps\*

