



FEATURES AND BENEFITS

- Units are shipped with die cast aluminum joiners installed for suspension and structural continuity.
- Aircraft grade suspension cables available in 24" - 50" (L)s.

APPLICATIONS

Open office ambient lighting for virtually glare free and shadow free illumination.

OPTIONS

This fixture is available with several options of feed kits with electrical cord, non-feed kits with no electrical cord and end caps that are sold separately and required for assembly. Speak to a sales representative for assistance with configuring the right fixture for you.

DIRECT/INDIRECT PENDANT

PDI-2-F28T5-MV • 91000

Direct/Indirect Pendant
White Powder Finish
56.5" (L) • 7.75" (W) • 2" (D) • Multi Volt
Uses Two F28T5 Lamps*

PDI-2-F54T5HO-MV • 91001

Direct/Indirect Pendant
White Powder Finish
56.5" (L) • 7.75" (W) • 2" (D) • Multi Volt
Uses Two F54T5HO Lamps*

PDI-3-F28T5-MV • 91002

Direct/Indirect Pendant
White Powder Finish
56.5" (L) • 7.75" (W) • 2" (D) • Multi Volt
Uses Three F28T5 Lamps*

PDI-3-F54T5HO-MV • 91003

Direct/Indirect Pendant
White Powder Finish
56.5" (L) • 7.75" (W) • 2" (D) • Multi Volt
Uses Three F54T5HO Lamps*

FEED KIT WITH ELECTRIC CORD

ITEM#	DESCRIPTION	LENGTH	CEILING TYPE
91075	PDI/FK/DW/24IN	24"	DRYWALL
91076	PDI/FK/DW/36IN	36"	DRYWALL
91077	PDI/FK/DW/50IN	50"	DRYWALL
91078	PDI/FK/DC/24IN	24"	DROP CEILING
91079	PDI/FK/DC/36IN	36"	DROP CEILING
91080	PDI/FK/DC/50IN	50"	DROP CEILING

NON-FEED KIT NO ELECTRIC CORD

ITEM#	DESCRIPTION	LENGTH	CEILING TYPE
91081	PDI/NFK/DW/24IN	24"	DRYWALL
91082	PDI/NFK/DW/36IN	36"	DRYWALL
91083	PDI/NFK/DW/50IN	50"	DRYWALL
91084	PDI/NFK/DC/24IN	24"	DROP CEILING
91085	PDI/NFK/DC/36IN	36"	DROP CEILING
91086	PDI/NFK/DC/50IN	50"	DROP CEILING

END CAP

DESCRIPTION	ITEM#
PDI/EC END-CAP FOR PDI FIXTURE	91050

