





















EXIT/EDGE/SU/1F/RC/WH/EM/NYC • 04327

Universal Surface Mount . White Housing 1 Faced Clear Plate • Red Letters

Emergency Backup Ballast • NYC Qualified 13" (H) • 15" (W) • 1.75" (D) • Universal Bracket Included

EXIT/EDGE/SU/1F/RC/WH/NYC • 04317

Universal Surface Mount • White Housing 1 Faced Clear Plate • Red Letters

Universal Bracket Included • NYC Qualified 13" (H) • 15" (W) • 1.75" (D)

EXIT/EDGE/SU/1F/RM/WH/EM/NYC • 04318

Universal Surface Mount . White Housing 1 Faced Mirrored Plate • Red Letters

Emergency Backup Ballast • NYC Qualified 13" (H) • 15" (W) • 1.75" (D) • Universal Bracket Included

EXIT/EDGE/SU/2F/RM/WH/EM/NYC • 04319

Universal Surface Mount . White Housing 2 Faced Mirrored Plate • Red Letters

Emergency Backup Ballast • NYC Qualified 13" (H) • 15" (W) • 1.75" (D) • Universal Bracket Included

EXIT/EDGE/RC/1F/RC/AL/EM/NYC • 04325

Recessed Ceiling Mount • Aluminum Housing

1 Faced Clear Plate • Red Letters

Emergency Backup Ballast • NYC Qualified 10" (H) • 17.5" (W) • 4" (D)

EXIT/EDGE/RC/1F/RM/WH/EM/NYC • 04330

Recessed Ceiling Mount . White Housing 1 Faced Mirrored Plate • Red Letters

Emergency Backup Ballast • NYC Qualified 10" (H) • 17.5" (W) • 4" (D)

EXIT/EDGE/RC/2F/RM/AL/EM/NYC • 04326

Recessed Ceiling Mount • Aluminum Housing

2 Faced Mirrored Plate • Red Letters

Emergency Backup Ballast • NYC Qualified 10" (H) • 17.5" (W) • 4" (D)

EXIT/EDGE/RC/2F/RM/WH/EM/NYC • 04331

Recessed Ceiling Mount . White Housing

2 Faced Mirrored Plate • Red Letters

Emergency Backup Ballast • NYC Qualified

10" (H) • 17.5" (W) • 4" (D)

EXIT PAGE 46 FIXTURES WWW.SOLOMONLIGHTING.ORG TEL: 212 255-4991



EXIT LIGHTS (IT-EMERGENCY COMBO

FEATURES AND BENEFITS

- · Energy efficient LED technology
- UL listed for damp locations & meets UL924, NFPA 101 Life Safety Code, NEC. OSHA, Local and State Codes
- · Dual 120V/277V voltage
- · Long-life, maintenance-free, rechargeable NiCd battery
- · Internal solid-state transfer switch automatically connects the internal battery to LED Board/lamp heads for minimum 90-minute emergency illumination
- Fully automatic solid-state, two-rate charger initiates battery charging to recharge a discharged battery in 24 hours.



- Standard with three ultra-bright LED emergency lighting lamp heads

 (H)-performance smooth aluminum
- reflector and tempered glass lens for optimal light distribution.
- · Ultra-bright, energy eiffcient Red LED (exit sign illumination)







EXIT/SU/1-2F/R/W/EM • 04308 Universal Surface Mount • Emergency Backup 1 or 2 Faced White Plate

White Plastic Housing • Red Letters 10.5" (H) • 14.5" (W) • 2.25" (D) • Universal Bracket Included



EXIT/SU/1-2F/R/W/ES • 04311

Universal Surface Mount • 1 or 2 Faced White Plate White Plastic Housing • Red Letters • Energy Star Qualified

10.5" (H) • 14.5" (W) • 2.25" (D) • Universal Bracket Included



EXIT/SU/1F/R/W/COMBO/2H • 04303

Universal Surface Mount • 2 Head

1 Faced White Plate

White Plastic Housing • Red Letters 15.5" (H) • 14.5" (W) • 4" (D) • Universal Bracket Included



EXIT/SU/1-2F/R/W/EM/NYC • 04307

Universal Surface Mount • Emergency Backup 1 or 2 Faced White Plate . NYC Qualified

White Heavy Duty Steel Housing . Red Letters 10.5" (H) • 14.5" (W) • 2.25" (D) • Universal Bracket Included



EXIT/SU/1-2F/R/W/NYC • 04316

Universal Surface Mount . NYC Qualified 1 or 2 Faced White Plate

White Heavy Duty Steel Housing • Red Letters 10.5" (H) • 14.5" (W) • 2.25" (D) • Universal Bracket Included







EXIT/SU/1F/R/W/COMBO/3H/NYC • 04306

Universal Surface Mount • 3 Head**

1 Faced White Plate • NYC Qualified White Heavy Duty Steel Housing • Red Letters

15.5" (H) • 14.5" (W) • 4" (D) • Universal Bracket Included

**This fixture may be used with only 2 heads.

Unassembled additional head included.











FEATURES AND BENEFITS

· Heavy duty construction • UL listed for damp locations & meets UL924, NFPA 101 Life Safety Code, NEC, OSHA, Local and State Codes Dual 120V/277V voltage • Charge rate/power "ON" LED indicator light and push-to-test switch for mandated code compliance testing • LVD (low voltage disconnect) prevents battery from deep discharge 6V, sealed lead acid, maintenance-free, rechargeable battery Internal solid-state transfer switch automatically connects the internal battery to lamp heads for minimum 90-minute emergency illumination • Fully automatic solid-state, two-rate charger initiates battery charging to recharge a discharged battery in 24 hours • Heavy 20-gauge steel construction • White powder-coated finish Side and top conduit knockouts • Thermoplastic emergency lamp heads Adjustable, glare-free PAR-Type lamp heads

EMERGENCY LIGHT



A. EMER/6V/2H/18W • 04304 2 Head • 6 Volt Battery

18 Watt Capacity • Two 9 Watt Lamps Included 9" (H) • 10" (W) • 2.5" (D)

EMER/6V/2H/18W/NYC • 04305

NYC Qualified • 2 Head • 6 Volt Battery

18 Watt Capacity • Two 9 Watt Lamps Included

9" (H) • 10" (W) • 2.5" (D)



B. EMER/6V/3H/27W/NYC • 04309

NYC Qualified • 3 Head • 6 Volt Battery
27 Watt Capacity • Three 9 Watt Lamps Included
9" (H) • 10" (W) • 2.5" (D)



XTR/RFBK3RA • 00001 Red LED Exit Light Retrofit Kit

2.8 Watt • Candelabra Base

DC and Intermediate Socket Adapters Included 2 Pack



EXIT

FIXTURES WWW.SOLOMONLIGHTING.ORG TEL: 212 255-4991 PAGE 48

B.